

LanXPLORED Pro

Upgrade Instruction



LanXPLORED Software Release Notes Brief

Summary:

Release v2.0.55 replaces the previous production release (v2.0.48) for previous version of LanXPLORED Pro.

Main changes for LanXPLORED Pro:

- New and enhanced functionality
 - Support new version Edimax 7811un V2 nano USB-Wi-Fi dongle for AnyWare.
 - Added Japanese language support
 - Support TP Link nano USB-Wi-Fi dongle (TL-WN725N ver 3.0) for AnyWare to comply Japanese regulation
 - Support TP Link Archer T2U Plus AC600 USB-Wi-Fi dongle for Wi-Fi test to comply Japanese regulation
- Bug fixes
 - None

LanXPLOER Software Update Instruction

CATION:

All saved data will be erased after upgrading. Please make sure all your data is backed up before upgrading.

To update units fitted with software older than v1.0.13:

1. Copy the file LanXPLOERER.bin to the root directory of a USB memory key
2. Ensure that the tester is connected to the mains power supply, or that the battery is fully charged
3. Switch the tester ON
4. Insert the USB memory key into the tester
5. Save any results stored in the tester (all data and settings will be lost following the software update) via USB memory key
6. From the HOME screen, select F4(SETUP) / SYSTEM / UPDATE
7. Select F1 (UPDATE)
8. Wait for the update to be completed
9. Update to the current version as described below

To update units fitted with v1.0.13 or later to the current software version (v2.0.55 or later):

1. Copy the file LanXPLOERER-md5.bin to the root directory of a USB memory key
2. Ensure that the tester is connected to the mains power supply, or that the battery is fully charged
3. Switch the tester ON
4. Insert the USB memory key into the tester
5. Save any results stored in the tester (all data and settings will be lost following the software update) via memory key
6. From the HOME screen, select F4(SETUP) / SYSTEM / UPDATE
7. Select F1 (UPDATE)
8. Wait for the update to be completed then
9. Make a factory default reset to select F4(SETUP) / SYSTEM / FACTORY
10. Select F1 (RESET)
11. Wait for the reset to be completed
12. Now the unit ready to use.

To use (Wi-Fi) 5GHz dual band Wi-Fi test functions

You need to have a dedicated external USB Wi-Fi adapter - *EDIMAX EW-7811UAC* or *TP Link Archer T2U Plus AC600*

To use (Wi-Fi) report transfer to mobile devices (smart phone, tablet)

You need to have a dedicated USB Wi-Fi adapter – *EdiMax EW-7811Un V2* or *TP Link TL-WN725N* and download the free IDEAL AnyWARE APP (iOS or Android) to smartphone or tablet.